


| PINOUT | PIN | DESCRIP |
|--------|-----|---------|
| UR | 1 | |
| LR | 2 | |
| SENSE | 3 | |
| UL | 4 | |
| LL | 5 | |



SPACER DOT DETAIL

| QTY | ITEM NO | PART NUMBER | DESCRIPTION |
|-----|---------|-------------|-----------------------------------|
| 1 | 7 | 2500127 | CONNECTOR |
| 1 | 6 | ASD 7600100 | TAIL STRAIN RELIEF |
| 1 | 5 | ASD 6100489 | TOPSHEET SUBASSY |
| A/R | 4 | 4600127 | ZA SENSE INTERCONNECT (NOT SHOWN) |
| 1 | 3 | ASD 7900360 | TAIL SUBASSY |
| 1 | 2 | ASD 3700677 | GASKET SUBASSY |
| 1 | 1 | ASD 5800519 | BOTTOM SUBASSY |

- NOTES:
1. SPACER DOTS: .004 [1.0] X .140 [3.56] (FINGER INPUT) (NOT SHOWN)
 2. TOPSHEET: ANTIGLARE
 3. TOTAL THICKNESS: .074 [1.88] ±10%
 4. FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
 5. LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
 6. CONNECTOR: 5 POS, .10 PITCH, AMP 487378-4

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.
 DEC. TOLERANCE:
 .XX = ±.060 UNO FRACTIONAL X/X = ±1/16
 .XXX = ±.020 UNO
 .XXXX = ±.015 UNO ANGULAR TOL. = ±1°
 .XXXXX = ±.008 UNO



TOUCH INTERNATIONAL
 2222 West Rundberg Ln #100
 Austin, Texas 78758
 512-832-8292