



PINDOUT	
PIN	DESCRIP
1	LL
2	UL
3	SENSE
4	UR
5	LR

QTY	ITEM NO	PART NUMBER	DESCRIPTION
1	1	5800383	BOTTOM SUBASSY (GLASS)
1	2	3700523	GASKET SUBASSY
1	3	7900300	TAIL SUBASSY (FPC)
1	4	4600127	ZA SENSE INTERCONNECT (NOT SHOWN)
1	5	6100358	TOPSHEET SUBASSY
1/1	6	7600100 / 7600116	TAIL STRAIN RELIEF
1	7	2500108	CONNECTOR

FINISHED PART #	DO NOT SCALE DRAWING! UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES. DEC. TOLERANCE: .XX = ±.060 UNO FRACTIONAL TOL. X/X = ±1/16 .XXX = ±.020 UNO .XXXX = ±.015 UNO .XXXXX = ±.008 UNO
NEXT ASSY #	TOUCH INTERNATIONAL 2222 West Rundberg Ln #100 Austin, Texas 78758 512-832-8292



DRAWN DATE: R. Johnson 9/08
SCALE: NTS
SIZE: A
DVG. NO.: 48-F-5-121-004
REV.: 2.0

- NOTES:
1. SPACER DOTS: .004 [0.10] X .140 [3.56] (FINGER INPUT) (NOT SHOWN)
 2. TOPSHEET FINISH: BROAD BAND, INDEX MATCHED, ANTIGLARE (W/ HARDCOAT)
 3. TOTAL THICKNESS: .136 [3.45] ±10%
 4. FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
 5. LABEL: SERIAL #, PART # & REV. (FAR SIDE OF TAIL)
 6. LABEL: TI LABEL SPEC #6600099, TYPE 2, SIZE STANDARD (LOCATE APPROX WHERE SHOWN)
 7. CONNECTOR: 5 POS, .10 PITCH, AMP 487526-4
 7. REFERENCE DELIVERY SPECIFICATION 6500244 REV 2.0