



PIN	DESCRIP	THK
1	LR SENSE	.003 THK
2	UR SENSE	.004 THK
3	UL	.125 THK
4	LL	
5		

QTY	ITEM NO	PART NUMBER	DESCRIPTION
1	7	2500127	CONNECTOR
1	6	ASD 7600100	TAIL STRAIN RELIEF
1	5	ASD 6100433	TOPSHEET SUBASSY
1	4	4600127	ZA SENSE INTERCONNECT (NOT SHOWN)
1	3	ASD 7900360	TAIL SUBASSY
1	2	ASD 3700633	GASKET SUBASSY
1	1	ASD 5800459	BOTTOM SUBASSY

FINISHED PART #

DO NOT SCALE DRAWING!

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.

DEC. TOLERANCE:

.xxx = ±.060 UNO FRACTIONAL X/X = ±1/16

.xxxx = ±.020 UNO

.xxxxx = ±.015 UNO ANGULAR TOL. = ±1°

xxxxxx = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS

THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

DRAWN DATE: R. Johnson 5/08

SCALE: NTS

SHEET 1 OF 1

TITLE: SENSOR RES SW

2222 West Rundberg Ln #100
Austin, Texas 78758
512-832-8292

DWG. NO: 48-F-5-122-004

REV: 2.0

- NOTES:
1. SPACER DOTS: .004 [.10] X .140 [3.56] (PEN/FINGER INPUT)
 2. FINISH: ANTIGLARE
 3. TOTAL THICKNESS: .136 [3.46] ±.10%
 4. FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
 5. LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
 6. LABEL: TI LABEL SPEC #6600099, TYPE 2, SIZE STANDARD (LOCATE APPROX WHERE SHOWN)
 7. CONNECTOR: SR HEADER, 5 POS, .10 PITCH, AMP 487378-4
 8. REFERENCE DELIVERY SPECIFICATION 6500244
 9. ENVIRONMENTAL: ROHS COMPLIANT
- SPACER DOT DETAIL
-
- STACK-UP
- TOUCH SIDE
- TOUCH SIDE VIEW
- STACK-UP CONNECTOR NOT SHOWN
- 4 3 2 1
- ACAD