



1	1	2500127	CONNECTOR	
1	6	ASD 7600100	TAIL STRAIN RELIEF	
1	5	ASD 6100154	TOPSHEET SUBASSY	.007 THK
A/R	4	4600127	ZA SENSE INTERCONNECT (NOT SHOWN)	
1	3	ASD 7900148	TAIL SUBASSY	.003 THK
1	2	ASD 3700161	GASKET SUBASSY	.004 THK
1	1	ASD 5800186	BOTTOM SUBASSY	.093 THK
QTY	ITEM NO	PART NUMBER	DESCRIPTION	

FINISHED PART #

DO NOT SCALE DRAWING!
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.
REMOVE ALL BURRS AND BREAK SHARP EDGES.
DEC. TOLERANCE:
.XX = ±.060 UNO FRACTIONAL X/X = ±1/16
.XXXX = ±.015 UNO ANGULAR TOL. = ±1°
.XXXXX = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS
THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

DRAWN DATE
R. Johnson 10/04

SCALE: NTS

SIZE A

48-F-5-149-003

REV. 2.0

TOUCH INTERNATIONAL
2222 West Rundberg Ln #100
Austin, Texas 78758
512-832-8292

SENSOR RES SW
14.9 DIAG

- NOTES:
1. SPACER DOTS: .004 [1.0] X .140 [3.56] (FINGER INPUT) (NOT SHOWN)
 2. TOPSHEET: ANTIGLARE
 3. TOTAL THICKNESS: .104 [2.64] ±10%
 4. FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
 5. LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
 6. CONNECTOR: 5 POS, .10 PITCH, AMP 487378-4