

STACK-UP


STACK-UP  
(CONNECTOR NOT SHOWN)

PIN	DESCRIP
1	UL
2	UR
3	SENSE
4	LR
5	LL

QTY	ITEM ND	PART NUMBER	FINISHED PART #	DESCRIPTION
1	7	2500127		CONNECTOR
1	6	ASD 7600102		TAIL STRAIN RELIEF
1	5	ASD 6100183		TOPSHEET SUBASSY
A/R	4	4600127		ZA SENSE INTERCONNECT (NOT SHOWN)
1	3	ASD 7900170		TAIL SUBASSY
1	2	ASD 3700194		GASKET SUBASSY
1	1	ASD 5800196		BOTTOM SUBASSY
				.003 THK
				.004 THK
				.093 THK

DO NOT SCALE DRAWING. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.  
DEC. TOLERANCE:  
.XX = ±.060 UNO, FRAC. TOL. X/Y = ±1/16  
.XXX = ±.020 UNO  
.XXXX = ±.015 UNO  
.XXXXX = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS  
THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.



**TOUCH INTERNATIONAL**  
2222 West Rundberg Ln #100  
Austin, Texas 78758  
512-832-8292

TITLE: **SENSOR RES SW**  
15.0 DIAG

- NOTES:
1. SPACER DOTS: .004 [1.10] X .140 [3.56] (PEN/FINGER INPUT) (NOT SHOWN)
  2. TOPSHEET: ANTI-GLARE
  3. TOTAL THICKNESS: .104 [2.64] ±10%
  4. FLEX/TAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
  5. LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
  6. CONNECTOR: 5 POS, .10 PITCH, AMP 487378-4