

STACK-UP


STACK-UP  
(CONNECTOR NOT SHOWN)

PIN	DESCRIP
1	UR
2	LR
3	SENSE
4	UL
5	LL

1	7	2500127	CONNECTOR	
1	6	ASD 7600102	TAIL STRAIN RELIEF	
1	5	ASD 6100183	TOPSHEET SUBASSY	.007 THK
A/R	4	4600127	ZA SENSE INTERCONNECT (NOT SHOWN)	
1	3	ASD 7900153	TAIL SUBASSY	.003 THK
1	2	ASD 3700194	GASKET SUBASSY	.004 THK
1	1	ASD 5800196	BOTTOM SUBASSY	.093 THK
QTY	ITEM ND	PART NUMBER	DESCRIPTION	
	FINISHED PART #		NEXT ASSY #	

DO NOT SCALE DRAWING.  
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.  
 REMOVE ALL BURRS AND BREAK SHARP EDGES.  
 DEC. TOLERANCE:  
 .XX = ±.060 UNO. FRAC. TOL. X/Y = ±1/16  
 .XXX = ±.020 UNO  
 .XXXX = ±.015 UNO ANGLUAR TOL. = ±1°  
 .XXXXX = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS  
 THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.



TITLE: SENSOR RES SW  
 15.0 DIAG

2222 West Rundberg Ln #100  
 Austin, Texas 78758  
 512-832-8292

- NOTES:
1. SPACER DOTS: .004 [ .10] X .140 [3.56] (PEN/FINGER INPUT) (NOT SHOWN)
  2. TOPSHEET: ANTIGLARE
  3. TOTAL THICKNESS: .104 [2.64] ±10%
  4. FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
  5. LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
  6. CONNECTOR: 5 POS. .10 PITCH, AMP 487378-4