



PINOUT	
PIN	DESCRIP
1	UR
2	LR
3	SENSE
4	UL
5	LL

QTY	ITEM NO	PART NUMBER	DESCRIPTION
1	7	2500127	CONNECTOR
1	6	ASD 7600102	TAIL STRAIN RELIEF
1	5	ASD 6100237	TOPSHEET SUBASSY
A/R	4	4600127	ZA SENSE INTERCONNECT (NOT SHOWN)
1	3	ASD 7900201	TAIL SUBASSY
1	2	ASD 3700285	GASKET SUBASSY
1	1	ASD 5800253	BOTTOM SUBASSY

FINISHED PART #

DO NOT SCALE DRAWING!

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.

DEC. TOLERANCE:

.XX = ±.060 UNO FRAC. TOL. X/X = ±1/16

.XXX = ±.020 UNO

.XXXX = ±.015 UNO ANGULAR TOL. = ±1°

XXXXX = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS

THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

DRAWN DATE: 12/04

SCALE: NTS

SHEET 1 OF 1

TITLE: SENSOR RES SW

2222 West Rundberg Ln #100
Austin, Texas 78758
512-832-8292

- NOTES:
1. SPACER DOTS: .004 [0.10] X .140 [3.56] (FINGER INPUT) (NOT SHOWN)
 2. TOPSHEET: ANTIGLARE
 3. TOTAL THICKNESS: .136 [3.45] ±.10%
 4. FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
 5. LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
 6. CONNECTOR: 5 POS, .10 PITCH, AMP 487378-4