



PINOUT	
PIN	DESCRIP
1	UR
2	LR
3	SENSE
4	UL
5	LL

QTY	ITEM NO	PART NUMBER	DESCRIPTION
1	7	2500127	CONNECTOR
1	6	ASD 7600100	TAIL STRAIN RELIEF
1	5	ASD 6100157	TOPSHEET SUBASSY
A/R	4	4600127	ZA SENSE INTERCONNECT (NOT SHOWN)
1	3	ASD 7900150	TAIL SUBASSY
1	2	ASD 3700164	GASKET SUBASSY
1	1	ASD 5800164	BOTTOM SUBASSY

FINISHED PART #		DO NOT SCALE DRAWING!	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.
XXX	= ±.060 UNO	FRACTION	X/X = ±1/16
.XXXX	= ±.020 UNO	DECIMAL	ANGULAR TOL. = ±1°
.XXXXX	= ±.008 UNO	ANGULAR	



TOUCH INTERNATIONAL  
 2222 West Rundberg Ln #100  
 Austin, Texas 78758  
 512-832-8292

NOTICE OF PROPRIETARY RIGHTS  
 THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

- NOTES:
1. SPACER DOTS: .004 [1.0] X .140 [3.56] (FINGER INPUT) (NOT SHOWN)
  2. TOPSHEET: ANTIGLARE
  3. TOTAL THICKNESS: .104 [2.64] ±10%
  4. FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
  5. LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
  6. CONNECTOR: 5 POS, .10 PITCH, AMP 487378-4