



PINOUT	DESCRIP
1	UR
2	LR
3	SENSE
4	UL
5	LL

QTY	ITEM NO	PART NUMBER	DESCRIPTION
1	7	2500127	CONNECTOR
1	6	ASD 7600102	TAIL STRAIN RELIEF
1	5	ASD 6100271	TOPSHEET SUBASSY
A/R	4	4600127	ZA SENSE INTERCONNECT (NOT SHOWN)
1	3	ASD 7900153	TAIL SUBASSY
1	2	ASD 3700198	GASKET SUBASSY
1	1	ASD 5800198	BOTTOM SUBASSY

FINISHED PART #		NEXT ASSY #	
DO NOT SCALE DRAWING!		TOUCH INTERNATIONAL	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.		2222 West Rundberg Ln #100	
REMOVE ALL BURRS AND BREAK SHARP EDGES.		Austin, Texas 78758	
DEC. TOLERANCE:		512-832-8292	
XX = ±0.060 UNO	FRACTIONAL TOL. X/XX = ±1/16		
XXX = ±0.020 UNO	ANGULAR TOL. = ±1°		
XXXX = ±0.015 UNO			
XXXXX = ±0.008 UNO			

NOTICE OF PROPRIETARY RIGHTS		DRAWN DATE	
THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.		11/05	
SCALE: NTS		SIZE	
SHEET 1 OF 1		48-F-5-200-005	
REV. 2.0		ACAD	

- NOTES:
1. SPACER DOTS: .006 [1.5] X .140 [3.56] DIAG (FINGER/PEN INPUT) (NOT SHOWN)
  2. TOPSHEET: ANTIGLARE, BROAD BAND, INDEX MATCHED
  3. TOTAL THICKNESS: .136 [3.45] ±10%
  4. FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
  5. LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
  6. CONNECTOR: 5-POS, .10 PITCH, AMP 487378-4

