



PINOUT	PIN DESCRIP
1	X-
2	Y+
3	X+
4	Y-

QTY	ITEM NO	PART NUMBER	DESCRIPTION	THICKNESS
1	5		TAIL STRAIN RELIEF	
1	4		TOPSHEET SUBASSY (AG)	
1	3		TAIL SUBASSY	.012 [0.3] THK @ EXPOSED
1	2		GASKET SUBASSY	
1	1		BOTTOMSHEET SUBASSY	.070 [1.8] THK

**FINISHED PART #**

**DO NOT SCALE DRAWING!**  
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.  
DEC. TOLERANCE:  
XX = ±.060 UNO FRACTIONAL TOL. X/X = ±1/16  
.XXXX = ±.020 UNO ANGULAR TOL. = ±1°  
XXXXX = ±.008 UNO

**NOTICE OF PROPRIETARY RIGHTS**  
THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

**TOUCH INTERNATIONAL**  
2222 West Rundberg Ln #100  
Austin, Texas 78758  
512-832-8292

**SENSOR RES 4W**  
10.4 DIAG

**SCALE: NTS**

**SIZE: A**

**DWG. NO: 48-F-4-104-003**

**REV: 2.1**

**ACAD**

- NOTES:**
- TOPSHEET FINISH: ANTI-GLARE
  - SPACER DOTS: .006 [0.15] X .160 [4.06] SPACING, PEN/FINGER INPUT (NOT SHOWN)
  - TOTAL THICKNESS: .083 [2.1] ±.008 [0.20]
  - FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
  - MATING CONNECTOR: 1.25MM PITCH ZIF
  - LABEL: SERIAL #, PART #, / REV (FAR SIDE OF TAIL)
  - LABEL: TI LABEL SPEC # 6600099 TYPE 1, SIZE SMALL (LOCATE APPROX. WHERE SHOWN)
- STACK-UP**