



PIN	PINDOUT	DESCRIP	BOTTOM
4	Y-	X+	RIGHT
3	X+	Y+	TOP
2	Y-	X-	LEFT
1			

QTY	ITEM NO	PART NUMBER	DESCRIPTION	THK
1	5		TAIL STRAIN RELIEF	
1	4		TOPSHEET SUBASSY (AG)	.007 [1.8] THK
1	3		TAIL SUBASSY	
1	2		GASKET SUBASSY	
1	1		BOTTOMSHEET SUBASSY (GLASS)	.043 [1.1] THK

FINISHED PART #
 DO NOT SCALE DRAWING!
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.
 REMOVE ALL BURRS AND BREAK SHARP EDGES.
 DEC. TOLERANCE:
 .XX = ±.060 UNO FRACTIONAL TOL. X/X = ±1/16
 .XXX = ±.020 UNO ANGULAR TOL. = ±1°
 .XXXX = ±.012 UNO
 .XXXXX = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS
 THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

DRAWN DATE: 5/09
 SCALE: NTS
 SHEET 1 OF 1

TITLE: TOUCH INTERNATIONAL
 2222 West Rundberg Ln #100
 Austin, Texas 78758
 512-832-8292

SENSOR RES 4W
 7.0 DIAG

- NOTES:
1. TOPSHEET FINISH: ANTI-GLARE
 2. SPACER DOTS: .006 [1.5] X .160 [4.0] SPACING, PEN/FINGER INPUT (NOT SHOWN)
 3. TOTAL THICKNESS: .054 [1.4] ±10%
 4. FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
 5. MATING CONNECTOR: 1.25MM PITCH ZIF
 6. LABEL: SERIAL#, PART# & REV. (FAR SIDE OF TAIL)
- LABEL: TI LABEL SPEC # 6600099 TYPE 1, SMALL (LOCATE APPROX. WHERE SHOWN)