



PIN	DESCRIP	YH	YH SENSE
1	YH	XL	XL SENSE
2	YL	YL	YL SENSE
3	XH	YL	YL SENSE
4	XL	YL	YL SENSE
5	YL	YL	YL SENSE
6	XH	YL	YL SENSE
7	XL	YL	YL SENSE
8	XH	YL	YL SENSE

STACK-UP

QTY	ITEM NO	PART NUMBER	FINISHED PART #
1	6	2500175	
A/R	5	8200100	
1	4	ASD 6100345	
1	3	ASD 3700509	
1	2	ASD 5800365	
1	1	ASD 1900333	

DO NOT SCALE DRAWING! UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES. DEC. TOLERANCE: .XX = ±.060 UNO FRACTIONAL TOL. X/X = ±1/16 .XXX = ±.020 UNO .XXXX = ±.015 UNO .XXXXX = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS  
THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

DRAWN DATE: R. Johnson 3/07  
SCALE: NTS  
SHEET 1 OF 1

TITLE: SENSOR RES 8W  
2222 West Rundberg Ln #100  
Austin, Texas 78758  
512-832-8292

- NOTES:
- SPACER DOTS: .004 [0.10] DIA. X .140 [3.56] SPACING (PEN/FINGER INPUT) (NOT SHOWN)
  - TOPSHEET FINISH: ANTIGLARE
  - TOTAL THICKNESS: .145 [3.68] ±10%
  - CONNECTOR: SR HEADER 8 POS. .10 CTRS LATCHING AMP# 487526-7
  - BACKER GLASS: CHEMICALLY STRENGTHENED
  - KAPTON TAPE TO ISOLATE TAIL TRACES
  - DO NOT BEND FLEXTAILS TO LESS THAN 1/4" RADIUS
  - LABEL: SERIAL#, PART#/REV (FAR SIDE OF TAIL)
  - LABEL: TI LABEL SPEC #6600099, TYPE 2, SIZE STANDARD (LOCATE APPROX WHERE SHOWN)