


REV	DESCRIPTION	ECD #	DFT	CHK	ENG	DATE
2.3	CHANGED PINOUT	0504053	JH			5/12/05




J1 PINOUT	
PIN	DESCRIP
1	LR
2	LL
3	SENSE/NC
4	UL
5	UR

J2 PINOUT	
PIN	DESCRIP
8	DRIVE 1
9	SHIELD
10	UR
11	LR
12	UL

- NOTES:
- TOTAL THICKNESS: .180 [4.6] ±10%
 - LABEL: SERIAL NUMBER & PART NUMBER / REV
 - CONNECTOR (J1): 5 POS, .10 PITCH, LATCH, AMP 104257-4
 - VLT @83% OR GREATER
 - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
 - STORAGE TEMP: -50°C TO +85°C, <35% RH
 - ETCH FINISH: AGO

1.4	6	1600138	HEATSHRINK, .75
1	5	7900101	NOVRAM CABLE 7"
31.0	4	8200100	TAPE, KAPTON, .50
A/R	3	7300100	SOLDER (NOT SHOWN)
1	2	7900175	TAIL SUBASSY
1	1	4000173	BOTTOM SUBASSY .125 THK
QTY	ITEM NO	PART NUMBER	DESCRIPTION

FINISHED PART #		NEXT ASSY #	
DO NOT SCALE DRAWING !			
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.			
DEC. TOLERANCE:			
.XX = ±.060 UNO		FRAC. TOL. x/x = ±1/16	
.XXX = ±.030 UNO		ANGULAR TOL. = ±1°	
.XXXX = ±.015 UNO		.XXXXX = ±.008 UNO	
NOTICE OF PROPRIETARY RIGHTS		 <p>TOUCH INTERNATIONAL 2222 West Rundberg Ln #100 Austin, Texas 78758 512-832-8292</p>	
THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.			
DRAWN DATE R. Johnson 2/04		TITLE: SENSOR CAP 5W 10.4 DIAG W/ NVRM	
SCALE: NTS	SIZE A	DWG. NO. 57-104FA-001-1	REV. 2.3
SHEET 1 OF 1		ACAD	