



REV	DESCRIPTION	ECD #	DFT	CHK	ENG	DATE
2.1	ADDED CABLE COLOR TO PINOUT CHART	0703173	S.S.R.			4/16/07

  

SECT. A-A STACK-UP

PINOUT	
PIN	DESCRIP
1 (RED)	UL
2 (GREEN)	UR
3 (ORANGE)	SENSE/NC
4 (BLACK)	LR
5 (WHITE)	LL

  

36.0	5	8200104	TAPE, KAPTON, 1.0
10.1	4	8200106	TAPE, KAPTON, .75
A/R	3	7300100	SOLDER (NOT SHOWN)
1	2	7900102	TAIL SUBASSY
1	1	4000202	BOTTOM SUBASSY .125 THK
QTY	ITEM NO	PART NUMBER	DESCRIPTION
FINISHED PART #		NEXT ASSY #	
DO NOT SCALE DRAWING !			
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.			
DEC. TOLERANCE:			
.XX = ±.060 UNO		FRAC. TOL. X/X = ±1/16	
.XXX = ±.030 UNO		ANGULAR TOL. = ±1°	
.XXXX = ±.015 UNO			
.XXXXX = ±.008 UNO			
NOTICE OF PROPRIETARY RIGHTS			
THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.			
DRAWN DATE JH 6/05			
SCALE: NTS		<b>TOUCH INTERNATIONAL</b> 2222 West Rundberg Ln #100 Austin, Texas 78758 512-832-8292	
SHEET 1 OF 1		TITLE: <b>SENSOR CAP 5W</b> 15.0 DIAG	
SIZE A	DWG. NO. 57-150FA-081	REV. 2.1	

- NOTES:
- TOTAL THICKNESS: .180 [4.6] ±10%
  - LABEL: SERIAL NUMBER & PART NUMBER / REV.
  - CONNECTOR: 5 POS, .10 PITCH, LATCH, AMP 487526-4
  - VLT @80% OR GREATER
  - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
  - STORAGE TEMP: -50°C TO +85°C, <35% RH
  - ETCH FINISH: AGO