


J2 PINOUT	
PIN	DESCRIP
8	DRIVE 1
8	SHIELD
9	UR
10	LR
11	UL
12	LL

J1 PINOUT	
PIN	DESCRIP
1	UL
2	UR
3	SENSE/NC
4	LR
5	LL

- NOTES:
- TOTAL THICKNESS: .128 [3.25] ±10%
 - FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
 - LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
 - CONNECTOR(J1): 5 POS, .10 PITCH, LATCH, AMP 487526-4
 - VLT @83% OR GREATER
 - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
 - STORAGE TEMP: -50°C TO +85°C, <35% RH

1.4	3	1600138	HEATSHRINK, .75
1	2	7900101	NOVRAM, 7"
1	1	57-170FA-012	SENSOR CAP 5W 17.0 DIAG
QTY	ITEM NO	PART NUMBER	DESCRIPTION
FINISHED PART #			NEXT ASSY #
DO NOT SCALE DRAWING ! UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES. DEC. TOLERANCE: .XX = ±.060 UNO FRAC. TOL. X/X = ±1/16 .XXX = ± .030 UNO ANGULAR TOL. = ±1° .XXXX = ± .015 UNO .XXXXX = ±.008 UNO			
NOTICE OF PROPRIETARY RIGHTS THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.			 TOUCH INTERNATIONAL 2222 West Rundberg Ln #100 Austin, Texas 78758 512-832-8292
DRAWN DATE R. Johnson 05/04			TITLE: SENSOR CAP 5W 17.0 DIAG W/ NVRM
SCALE: NTS		SIZE: A	DWG. NO. 57-170FA-012-1
SHEET 1 OF 1			REV. 2.0