



REV	DESCRIPTION	ECD #	DFT	CHK	ENG	DATE
-----	-------------	-------	-----	-----	-----	------

PINOUT	
PIN	DESCRIP
1	LL
2	LR
3	SENSE/NC
4	UR
5	UL

1	7	2500108	CONNECTOR
61.0	6	8200100	TAPE, KAPTON, .50
25.0	5	8200110	TAPE, KAPTON, .25
12.4	4	8200106	TAPE, KAPTON, .75
1	3	7600102	STRAIN RELIEF
1	2	7900223	TAIL SUBASSY
1	1	4000233	BOTTOM SUBASSY .125 THK
QTY	ITEM NO	PART NUMBER	DESCRIPTION
FINISHED PART #		NEXT ASSY #	

DO NOT SCALE DRAWING !
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.
 DEC. TOLERANCE:
 .XX = ±.060 UNO FRAC. TOL. x/x = ±1/16
 .XXX = ±.030 UNO
 .XXXX = ±.015 UNO ANGULAR TOL. = ±1°
 .XXXXX = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS
 THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.



TOUCH INTERNATIONAL
 2222 West Rundberg Ln #100
 Austin, Texas 78758
 512-832-8292

TITLE: SENSOR CAP 5W 18.0 DIAG			
DRAWN DATE R. Johnson 05/04	SCALE: NTS	SIZE A	DWG. NO. 57-180FA-002
SHEET 1 OF 1			REV. 2.2

- NOTES:
- TOTAL THICKNESS: .128 [3.25] ±10%
 - FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
 - LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
 - CONNECTOR: 5 POS, .10 PITCH, LATCH, AMP 487526-4
 - VLT @80% OR GREATER
 - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
 - STORAGE TEMP: -50°C TO +85°C, <35% RH
 - ETCH FINISH: AGO