



REV	DESCRIPTION	ECD #	DFT	CHK	ENG	DATE
-----	-------------	-------	-----	-----	-----	------

PINOUT	
PIN	DESCRIP
5	UR
4	UL
3	SENSE/NC
2	LL
1	LR

1	7	2500108	CONNECTOR
26.0	6	8200110	TAPE, KAPTON .25
13.0	5	8200106	TAPE, KAPTON .75
63.5	4	8200100	TAPE, KAPTON .50
1	3	7600102	TAIL STRAIN RELIEF
1	2	7900248	TAIL SUBASSY
1	1	4000240	BOTTOM SUBASSY .125 THK

QTY	ITEM NO	PART NUMBER	DESCRIPTION
-----	---------	-------------	-------------

FINISHED PART #	NEXT ASSY #
-----------------	-------------

DO NOT SCALE DRAWING !
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.
 DEC. TOLERANCE:
 .XX = ±.060 UNO FRAC. TOL. x/x = ±1/16
 .XXX = ±.030 UNO
 .XXXX = ±.015 UNO ANGULAR TOL. = ±1°
 .XXXXX = ±.008 UNO

TOUCH INTERNATIONAL
 2222 West Rundberg Ln #100
 Austin, Texas 78758
 512-832-8292

TITLE: **SENSOR CAP 5W**
 19.0 DIAG

NOTICE OF PROPRIETARY RIGHTS
 THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

DRAWN DATE
 R. Johnson 3/06

SCALE: NTS	SIZE: A	DWG. NO.: 57-190FA-042	REV.: 2.0
------------	---------	------------------------	-----------

- NOTES:
- TOTAL THICKNESS: .128 [3.25] ±10%
 - FLEXTAIL: DO NOT BEND TO LESS THAN 1/8" RADIUS
 - LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
 - CONNECTOR: 5 POS, .10 PITCH, LATCH, AMP 487526-4
 - VLT @83% OR GREATER
 - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
 - STORAGE TEMP: -50°C TO +85°C, <35% RH