



REV	DESCRIPTION	ECD #	DFT	CHK	ENG	DATE
2.1	ADDED CABLE COLOR TO PINOUT CHART	0703174	S.S.R.			4/17/07

PINOUT	
PIN	DESCRIP
1 (RED)	UL
2 (GREEN)	UR
3 (ORANGE)	SENSE/NC
4 (BLACK)	LR
5 (WHITE)	LL

QTY	ITEM NO	PART NUMBER	DESCRIPTION
32.0	6	8200110	TAPE, KAPTON .25
16.0	5	8200106	TAPE, KAPTON .75
52.0	4	8200100	TAPE, KAPTON .50
1	3	7300100	SOLDER (NOT SHOWN)
1	2	7900219	TAIL SUBASSY
1	1	4000201	BOTTOM SUBASSY .125 THK

**DO NOT SCALE DRAWING !**  
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.  
 DEC. TOLERANCE:  
 .XX = ±.060 UNO    FRAC. TOL. X/X = ±1/16  
 .XXX = ±.030 UNO  
 .XXXX = ±.015 UNO    ANGULAR TOL. = ±1°  
 .XXXXX = ±.008 UNO

**NOTICE OF PROPRIETARY RIGHTS**  
 THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.



**TOUCH INTERNATIONAL**  
 2222 West Rundberg Ln #100  
 Austin, Texas 78758  
 512-832-8292

TITLE: **SENSOR CAP 5W**  
 19.0 DIAG

DRAWN DATE R. Johnson 5/04	SCALE: NTS	SIZE A	DWG. NO. 57-190FA-061	REV. 2.1
-------------------------------	------------	-----------	--------------------------	-------------

- NOTES:
- TOTAL THICKNESS: .180 [4.6] ±10%
  - LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
  - CONNECTOR: 5 POS, .10 PITCH, LATCH, AMP 487526-4
  - VLT @80% OR GREATER
  - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
  - STORAGE TEMP: -50°C TO +85°C, <35% RH
  - ETCH FINISH: AGO