


REV	DESCRIPTION	ECD #	DFT	CHK	ENG	DATE
-----	-------------	-------	-----	-----	-----	------

J1 PINOUT		J2 PINOUT	
PIN	DESCRIP	PIN	DESCRIP
1	LR	8	DRIVE 1
2	LL	8	SHIELD
3	SENSE/NC	9	UR
4	UL	10	LR
5	UR	11	UL
		12	LL

QTY	ITEM NO	PART NUMBER	DESCRIPTION
	1.4	8	1600138 HEATSHRINK, .75
	1	7	7900101 NOVRAM, 7"
	17.0	6	8200106 TAPE, KAPTON, .75
	34.0	5	8200110 TAPE, KAPTON, .25
	52.4	4	8200100 TAPE, KAPTON, .50
	A/R	3	7300100 SOLDER (NOT SHOWN)
	1	2	7900102 TAIL SUBASSY
	1	1	4000199 BOTTOM SUBASSY .125 THK

FINISHED PART #		NEXT ASSY #	
DO NOT SCALE DRAWING !			
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.			
DEC. TOLERANCE:			
.XX = ±.060 UNO		FRAC. TOL. x/x = ±1/16	
.XXX = ±.030 UNO		ANGULAR TOL. = ±1°	
.XXXX = ±.015 UNO			
.XXXXX = ±.008 UNO			
NOTICE OF PROPRIETARY RIGHTS			
THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.			
DRAWN DATE JH 09/05		 <p>TOUCH INTERNATIONAL 2222 West Rundberg Ln #100 Austin, Texas 78758 512-832-8292</p>	
SCALE: NTS			
SHEET 1 OF 1		SIZE: A	DWG. NO.: 57-200FA-031-1
		REV.: 2.0	

- NOTES:
- TOTAL THICKNESS: .180 [4.6] ±10%
 - LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
 - CONNECTOR(J1): 5 POS, .10 PITCH, LATCH, AMP 487526-4
 - VLT @80% OR GREATER
 - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
 - STORAGE TEMP: -50°C TO +85°C, <35% RH
 - ETCH FINISH: AGO

SECT. B-B
STACK-UP
CABLE & CONNECTOR NOT SHOWN

SECT. A-A
STACK-UP