



PIN	DESCRIP	PINDUT
5	UR	UL
4	UL	UR
3	SENSE/NC	LL
2	LL	LR
1	LR	LL

QTY	ITEM NO	PART NUMBER	DESCRIPTION	FINISHED PART #	NEXT ASSY #
1	5	2500108	CONNECTOR		
2	4	7600116	STRAIN RELIEF		
1	3	7900248	TAIL SUBASSY		
1	2	8200119	TAIL INNERCONNECT		
1	1	4000306	GLASS ASSY. W/LPAT		

DO NOT SCALE DRAWING!  
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.  
 REMOVE ALL BURRS AND BREAK SHARP EDGES.  
 DEC. TOLERANCE:  
 .XX = ±.060 UNO FRACTIONAL X/X = ±1/16  
 .XXX = ±.030 UNO  
 .XXXX = ±.015 UNO ANGULAR TOL. = ±1°  
 .XXXXX = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS  
 THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

TOUCH INTERNATIONAL  
 2222 West Rundberg Ln #100  
 Austin, Texas 78758  
 512-832-8292

- NOTES:
- TOTAL THICKNESS: .128 [3.3] ±10% THICKNESS AT TAIL INTERCONNECT: .132 [3.35] ±10%
  - FLEXTAIL: INTEGRATION FOLDS ALLOWED
  - LABEL: SERIAL NUMBER & PART NUMBER / REV. (FAR SIDE OF TAIL)
  - CONNECTOR: 5 POS, .10 PITCH, LATCH, AMP 487526-4
  - VLT @83% OR GREATER
  - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
  - STORAGE TEMP: -50°C TO +85°C, <35% RH
  - ENVIRONMENTAL: RoHS COMPLIANT