



REV	DESCRIPTION	ECD #	DFT	CHK	ENG	DATE
-----	-------------	-------	-----	-----	-----	------

J1 PINDUT	
PIN	DESCRIP
1	LR
2	LL
3	SHIELD
4	UL
5	UR

J2 PINDUT	
PIN	DESCRIP
8	DRIVE 1
8	SHIELD
9	UR
10	LR
11	UL
12	LL

1.4	7	1600138	HEATSHRINK .75
1	6	7900101	NOVRAM 7"
20.0	5	8200110	KAPTON TAPE, .25 (ISOLATION)
72.0	4	8200100	KAPTON TAPE, .50 (ISOLATION)
A/R	3	7300100	SOLDER (5X) (NOT SHOWN)
1	2	7900219	TAIL SUBASSY
1	1	4000229	BOTTOM SUBASSY .125 THK
QTY	ITEM NO	PART NUMBER	DESCRIPTION

- NOTES:
- TOTAL THICKNESS: .180 [4.57] ±10%
 - LABEL: SERIAL NUMBER & PART NUMBER / REV.
 - CONNECTOR: 5 POS, .10 PITCH, LATCH, AMP 487526-4
 - VLT @83% OR GREATER
 - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
 - STORAGE TEMP: -50°C TO +85°C, <35% RH
 - 1/2 WAVE BACK COATED W/ BACK EMI BUSBAR
 - ETCH FINISH: AGO

DO NOT SCALE DRAWING !
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.
 DEC. TOLERANCE:
 .XX = ±.060 UNO FRAC. TOL. x/x = ±1/16
 .XXX = ±.050 UNO ANGULAR TOL. = ±1'
 .XXXX = ±.030 UNO
 .XXXXX = ±.008 UNO

NOTICE OF PROPRIETARY RIGHTS
 THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.



TOUCH INTERNATIONAL
 2222 West Rundberg Ln #100
 Austin, Texas 78758
 512-832-8292

TITLE:
SENSOR CAP 5W 15.0 DIAG
1/2 WAVE BK CT W/ NVRM

DRAWN DATE R. Johnson 3/06	SCALE: NTS	SIZE A	DWG. NO. 59-150FA-001-1	REV. 2.0
SHEET 1 OF 1		ACAD		