REV	DESCRIPTION	ECO #	DFT	CHK	ENG	DATE





PINOUT	
PIN	DESCRIP
1	UL
2	UR
3	SHIELD
4	LR
5	LL

NOTES:

1. TOTAL THICKNESS: .180 [4.57] ±10%
2. LABEL: SERIAL NUMBER & PART NUMBER / REV.
3. CONNECTOR: 5 POS, .10 PITCH, LATCH, AMP 487526-4
4. VLT @83% OR GREATER
5. OPERATING TEMP: –20°C TO +70°C, 5% TO 90% RH
6. STORAGE TEMP: –50°C TO +85°C, <35% RH
7. 1/2 WAVE BACK COATED W/ BACK EMI BUSBAR
8. ETCH FINISH: AGO

QTY	ITEM NO	PART NUMBER	DESCRIPTION
20.0	5	8200110	KAPTON TAPE, .25 (ISOLATION)
72.0	4	8200100	KAPTON TAPE, .50 (ISOLATION)
A/R	3	7300100	SOLDER (5X) (NOT SHOWN)
1	2	7900219	TAIL SUBASSY
1	1	4000229	BOTTOM SUBASSY .125 THK

FINISHED PART #

NEXT ASSY #

DO NOT SCALE DRAWING !

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.

DEC. TOLERANCE:
.XX = ±.060 UNO
.XXX = ± .050 UNO
.XXXX = ± .030 UNO
.XXXXX = ±.008 UNO

FRAC. TOL. X/X = ±1/16
ANGULAR TOL. = ±1°

NOTICE OF PROPRIETARY RIGHTS

THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.

DRAWN DATE
R. Johnson 2/06

SCALE: NTS

SHEET 1 OF 1

TOUCH INTERNATIONAL
2222 West Rundberg Ln #100
Austin, Texas 78758
512-832-8292

TITLE:
SENSOR CAP 5W 15.0 DIAG
1/2 WAVE BK COAT

SIZE	DWG. NO.	REV.
A	59-150FA-001	2.0

ACAD