


REV	DESCRIPTION	ECD #	DFT	CHK	ENG	DATE
-----	-------------	-------	-----	-----	-----	------

PINOUT	
PIN	DESCRIP
1	UL
2	UR
3	SHIELD
4	LR
5	LL

QTY	ITEM NO	PART NUMBER	DESCRIPTION
28.0	5	8200110	KAPTON TAPE, .25 (ISOLATION)
74.5	4	8200100	KAPTON TAPE, .50 (ISOLATION)
A/R	3	7300100	SOLDER (NOT SHOWN)
1	2	7900219	TAIL SUBASSY
1	1	4000227	BOTTOM SUBASSY .125 THK

FINISHED PART #		NEXT ASSY #	
DO NOT SCALE DRAWING !			
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. REMOVE ALL BURRS AND BREAK SHARP EDGES.			
DEC. TOLERANCE:			
.XX = ±.060 UNO		FRAC. TOL. x/x = ±1/16	
.XXX = ±.050 UNO		ANGULAR TOL. = ±1°	
.XXXX = ±.030 UNO			
.XXXXX = ±.008 UNO			
NOTICE OF PROPRIETARY RIGHTS			
THIS DOCUMENT, AND THE INFORMATION IT CONTAINS, IS PROPRIETARY TO TOUCH INTERNATIONAL. IT MUST NOT BE DUPLICATED, OR ITS CONTENTS USED OR DISCLOSED (IN WHOLE OR IN PART) WITHOUT WRITTEN PERMISSION FROM TOUCH INTERNATIONAL.			
DRAWN DATE R. Johnson 3/06		 <p>TOUCH INTERNATIONAL 2222 West Rundberg Ln #100 Austin, Texas 78758 512-832-8292</p>	
SCALE: NTS			
SHEET 1 OF 1		SIZE A	DWG. NO. 59-170FA-021
		REV. 2.0	

- NOTES:
- TOTAL THICKNESS: .180 [4.57] ±10%
 - LABEL: SERIAL NUMBER & PART NUMBER / REV.
 - CONNECTOR: 5 POS, .10 PITCH, LATCH, AMP 487526-4
 - VLT @83% OR GREATER
 - OPERATING TEMP: -20°C TO +70°C, 5% TO 90% RH
 - STORAGE TEMP: -50°C TO +85°C, <35% RH
 - 1/2 WAVE BACK COATED W/ BACK EMI BUSBAR
 - ETCH FINISH: AGO