

88-F-PMC-35-MDL-01

Extreme Touch Projected Capacitive Module

Touch International's 88-F-PMC-35-MDL-01 projected capacitive module is equipped with a general purpose projected capacitive controller and touch screen mounted on a 3.5" LCD.

Designed to interface with computer systems through a wide variety of standard interfaces, the 54-B-PMC-07-01 projected capacitive controller is compatible with USB, I2C and Serial communications. Combined with Touch International's proprietary firmware, the controller can easily be tuned to your custom design, as well as a range of different applications. Featuring single touch and gesture (two-finger touch) capabilities, the 54-B-PMC-07-01 controller can help take your application to the next level.

Features

Motion Detection Method	Capacitive Sensing
X/Y Position Reporting	Absolute Position
Touch Force	No Contact Pressure Required
HID	HID Compliant
Calibration	No Need for Calibration
Chip Set Solution	Available
Touch	Single Touch and Gesture (Two-Finger Touch)
RoHS	Compliant
REACH	Compliant
Warranty	Touch Screen - 10 Yrs. Controller - 5 Yrs.



Evaluation Kit Includes:

- **3.5" Touch Screen**
(88-F-PMC-35-008)
- **1 PSoC Controller Package**
(54-B-PMC-35-008)
- **LCD**
(8700173)
- **VGA Drive Kit**
(13B0103)
- **OSD Board**
(1500189)
- **Power Adapter**
(1500177)
- **USB Cable**
(1300264)
- **VGA Cable**
(1300277)

Applications

- **Mobile and Smart Phones**
- **PDAs**
- **Gaming Consoles**
- **Personal Media Players**
- **Digital Cameras**
- **Printers**

Touch Screen Specifications

Operating Temperature	-20 to 85°C
Storage Temperature	-40 to 85°C
Relative Humidity	50°C at 90% RH Non-Condensing
Controller Mean Time Between Failures	> 100 Million Touches

Controller Specifications

Controller Size	2.0" x 2.0" (50.80mm x 50.80mm)
Power Requirements	5 ~ 9V DC Unregulated Power, Typical 60mA
Operating Temperature	-40 to 85°C
Storage Temperature	-40 to 85°C
Relative Humidity	35°C at 95% RH Non-Condensing
Interface	USB: 2.0, 1.1 Compliant (Standard) Optional: USB-UART RS-232 Serial Communication Protocol: No Parity, 8 Data Bits, 1 Stop Bit, 15200 Baud, No Flow Control I2C Communication
Communication Cables	A Plug/5-Pin Mini-B Plug (USB & USB-UART): TI# 1300264
Resolution	2048 x 2048
Report Rate	Approx. 25 - 50 Points/Sec.
Mean Time between Failures	> 5.6 Million Hours
Supported Operating Systems	Windows 2000, XP, Vista and 7; Linux Ubuntu; Mac OSX

LCD Specifications

LCD Screen Size	3.5" Diagonal
Aspect Ratio	4:3
Brightness	250 cd/m ²
Contrast Ratio	400:1
Resolution	640 x 480 (Recommended)
Viewing Angle	+/- 50° Horizontal / +/- 50° Vertical
Response Time	15ms Rise / 25ms Fall
Pixel Pitch	0.1125 (H) mm X 0.1095 (V) mm
Outline Dimension	84.03 (W) mm X 65.24 (H) mm X 3.45 (D) mm (Typical)
Backlight	LED
Operating Temperature	-20~+70°C
Storage Temperature	-20~+70°C

LCD Drive Board Specifications

Video Input	Composite Signal Input and VGA Signal Input
Input Voltage	DC 5.0V +/- 0.2V (500mA +/- 30mA)
Operating Temperature	-10~+50°C
Storage Temperature	-20~+70°C

For additional information on Touch International products and solutions, contact a sales representative or e-mail sales@touchintl.com.